


MODEL NO.	MAXIMUM DRUM SIZE				EXTERNAL DIMENSIONS (mm)			WEIGHTS (kgs)		
	Dia	Width	Core Est.	Shaft	L	B	H	Tare	SWL	Gross
02-3000	32"	18"	16"	2" or 3"	3' 6" (1060)	3' 4" (1020)	4' 5" (1350)	600	900	1500
02-3600	36"	30"	18"	3"	4' 11" (1500)	3' 11" (1200)	4' 8" (1425)	700	1300	2000
02-4000	44"	36"	18"	3"	5' 4" (1630)	4' 4" (1350)	5' (1535)	1000	3500	4500
02-5000	50"	48"	25"	3"	6' 6" (1985)	5' (1535)	6' (1825)	1200	5000	6200
02-5500	55"	45"	25"	3"	6' 6" 1985	5' 5" 1650	6' 1" 1839	1300	7000	8300
02-6500	65"	48"	25"	3"	7' 1" (2150)	6' 3" (1910)	6' 7" (2010)	1600	8400	10,000
02-7500	75"	57"	32"	3" or 4"	7' 10" (2435)	8' (2275)	7' 5" (2400)	2000	9000	11,000
02-8500	82"	62"	41"	4"	9' 2" (2800)	7' 8" (2350)	7' 5" (2260)	2300	10,200	12,500
02-9600	96"	64"	42"	4"	9' 2" (2800)	10' 3" (3140)	9' 9" (2975)	2500	12,000	14,500

All spoolers are manufactured to meet DNV 2.7-1 / EN 27109 (CE  – II 3 G 11B T4) specifications and meet LOLER and PUWER regulations.

The spoolers can be supplied with the following features:

- Trollex Facility
- Earth Bosses
- Hydraulic Slip Line Ring (up to 5 hydraulic lines)
- 2", 3" or 4" Shafts
- Spares Kit
- Area for storing the Sheave Wheel
- Roof Bars to prevent Slings from snagging or catching
- Tie Back Facility to ensure the Spooler is secure
- Air Controls – On/Off & Air Regulator
- Emergency Stop Button
- Dual Air Inlets to suit a variety of Air Connections
- Drum Locking System
- Adjustable Drive Arms

BlueManta International Limited

5 Kirkton Avenue, Pitmedden Road Ind. Estate, Dyce, Aberdeen, AB21 0BF
Tel: 01224 775576 Email: info@bluemanta.com www.bluemanta.com